

"TECHNO" BRAND SUBMERSIBLE PUMPSETS - SUITABLE FOR 175 MM BOREWELL & ABOVE

Approximate Performance Chart at 2880 RPM, 380-415 Volts Three Phase, 50Hz, A.C. Supply

MOTOR : COPPER ROTOR · PUMP : BOWL - CAST IRON · IMPELLER - STAINLESS STEEL

TYPE : TMV-25		OUTLET SIZE 100 mm	DISCHARGE IN LPM					
HP	STAGE		0	680	810	950	1030	1190
7.50	3	HEAD IN METER	40	39	36	33	30	24
10.00	4		54	52	48	44	40	32
12.50	5		67	65	60	55	50	40
15.00	6		81	78	72	66	60	48

TYPE : TMV-40		OUTLET SIZE 100 mm	DISCHARGE IN LPM					
HP	STAGE		0	950	1110	1200	1320	1470
7.50	2	HEAD IN METER	27	26	24	22	20	16
12.50	3		40	39	36	33	30	24
15.00	4		54	52	48	44	40	32
20.00	5		67	65	60	55	50	40

TYPE : TMV-30		OUTLET SIZE 100 mm	DISCHARGE IN LPM					
HP	STAGE		0	900	960	1100	1180	1350
6.00	2	HEAD IN METER	27	26	24	22	20	16
10.00	3		40	39	36	33	30	24
12.50	4		54	52	48	44	40	32
15.00	5		67	65	60	55	50	40

TYPE : TMV-50		OUTLET SIZE 100 mm	DISCHARGE IN LPM					
HP	STAGE		0	1140	1270	1380	1550	1640
10.00	2	HEAD IN METER	27	26	24	22	20	16
15.00	3		40	39	36	33	30	24
20.00	4		54	52	48	44	40	32
25.00	5		67	65	60	55	50	40